


## TRB-FFAP

**Polyethylene glycol esterified with nitroterephthalic acid, bonded and crosslinked phase.**

- 100% Polyethylene glycol (PEG) esterified with nitroterephthalic acid
- Ideal for analysis of free acids (without derivatization), phenols and glycols
- High thermal stability (250°C)



### TRB-FFAP Equivalent Phase

**Agilent:** HP-FFAP, DB-FFAP, CP-WAX 58 CB  
**Supelco:** NUKOL, SP-1000  
**Restek:** STABILWAX-DA  
**SGE:** BP-21  
**Quadrex:** 007-FFAP

### TRB-FFAP

Internal Length	Film	Temp	Part.
Diam. (mm)	Thickness (µm)	limits (°C)	N°. (P/N)
<b>0,10</b>	10	0,10	40 to 240/250 <b>TR-150141</b>
	10	0,20	40 to 240/250 <b>TR-152141</b>
	15	0,10	40 to 240/250 <b>TR-150111</b>
	20	0,10	40 to 240/250 <b>TR-150181</b>
<b>0,20</b>	15	0,30	40 to 240/250 <b>TR-152119</b>
	30	0,30	40 to 240/250 <b>TR-152139</b>
	60	0,30	40 to 240/250 <b>TR-152169</b>
<b>0,25</b>	15	0,25	40 to 240/250 <b>TR-150212</b>
	30	0,25	40 to 240/250 <b>TR-150232</b>
	60	0,25	40 to 240/250 <b>TR-150262</b>
<b>0,32</b>	15	0,25	40 to 240/250 <b>TR-150213</b>
	15	0,50	40 to 240/250 <b>TR-150513</b>
	30	0,25	40 to 240/250 <b>TR-150233</b>
	30	0,50	40 to 240/250 <b>TR-150533</b>
	60	0,25	40 to 240/250 <b>TR-150263</b>
	60	0,50	40 to 240/250 <b>TR-150563</b>
<b>0,53</b>	15	0,50	40 to 240/250 <b>TR-150515</b>
	15	1,00	40 to 230/240 <b>TR-151015</b>
	30	0,50	40 to 240/250 <b>TR-150535</b>
	30	1,00	40 to 230/240 <b>TR-151035</b>
	60	0,50	40 to 240/250 <b>TR-150565</b>
	60	1,00	40 to 230/240 <b>TR-151065</b>